

Dear Customer,

with the purchase of a CELINA brick slips from the VINTAGE series, you have chosen a high-quality, durable product "Made in Germany".

Please note that the VINTAGE series has intentional breakages and irregularities in the surface as standard.

Attention: As with genuine reclaimed bricks, you will find not only full brick slips but also irregular broken pieces in the packaging

This is intended and desired, serving as true masonry with the charm of exposed brickwork in a traditional "reclaimed style".

Instructions for use

- Please check the brick slips before installing (Correct color? Correct article? Color and size of corners and flats matching together?)
- The substrate should be clean, dust free, workable, solid and even. Any wallpaper or other residues should be removed before installing the brick slips.
- We recommend priming the substrate.
- If required remove any loose residues from the back of the brick slip (e.g. with a wire brush).
- Spread a suitable flexible adhesive with a toothed spreader by “buttering” both on the back of the slip and on the wall ("buttering-floating").
- Press the brick slips into the adhesive bed with slightly sliding sideways movements, so that they are surrounded by the adhesive completely.
- Always mix the slips from several packages and several pallets.
- If desired, grout traditionally with jointing iron and tiling grout after 24 hours. Always process horizontal and vertical joints together promptly.
- If you want a less rustic look of the VINTAGE brick slips, you can easily reduce the light "VINTAGE layer" on the surface with a wire brush (also available as attachment for the drilling machine) and change the color more and more back to the original brick color.